

### **Product Sheet**

MIMO is a true demountable glass partition system offered in single and double glazing within the same extrusion. The line is exceptionally versatile and can accommodate any architectural needs including transoms and clerestories, almost limitless ceiling heights, solid panels, freestanding partitions, and a wealth of door types including framed and frameless swing and sliding, as well as a unique pocket sliding door.

## **Extrusions**



# MIMO

#### **Glazing and Panels:**

Single and double glazing
Thickness: ½" and ¾"
Tempered, laminated, low iron (extra clear), and speciality glass
Solid panels

#### Tolerance:

Total of 1-14"

#### Junctions:

Available in aluminum and polycarbonate Glass to glass, corner (L), and T condition

#### Profile:

Stick built

Profile dimensions:

- Top and bottom extrusion: W3" x H1-%16"
- Sliding single or double glazed door adds W<sup>15</sup>/<sub>16</sub>"

Same extrusion for centered, offset, and double glazing

Aluminum

Applied and integrated mullions available Aluminum and wood flyby available

#### Gaskets:

Door: available in black, white, and clear Wall: available in black, white, and grey

#### Ceiling Condition:

Can be installed on a bulk ceiling, acoustical tiles (ACT), or as a free-standing system Maximum height of 10'

20'+ with clerestory and transom available

#### Doors:

#### Frameless

- Single glazed sliding door
- Single glazed hinged door
- Single glazed pivot door

#### Framed

- Standard Muraflex single glazed pivot door
- Standard Muraflex double glazed pivot door

#### Wood

- Hinge door
- Pivot door

#### Standard door hardware

- Lever or ladder pull
- Locking or non-locking
- Drop seal available on framed and wood doors
- Hold open available on all swing doors Maximum door height: 10'

#### Acoustical properties:

Single glazed tested STC assembly score ranges (depending on options): 34 - 38
Double glazed tested STC assembly score ranges (depending on options): 43 - 46

#### Integrated electrical components:

High and low voltage wiring Integrated electrical components including room scheduler, card reader, and electrical strike available

Panic hardware available

#### Lead times:

6-8 weeks on standard clear anodized 8-10 weeks on custom system





# **Sustainability**

At Muraflex, we are dedicated to diminishing our impact on the environment. We are also committed to continually improving our procedures in terms of product development, supply, packaging and distribution in an effort to minimize our environmental footprint.













# **The Finishes**


Black anodized



Architectural



Medium Bronze anodized



Champagne anodized



Light Bronze anodized



Clear anodized



Black



Charcoal powder coat



Grey



Champagne



White



Custom powder Coat



Due to variances in screen calibration or print quality, finish images may not accurately represent the actual color sample.